061 STATE OF WASHINGTON AER211 7061 (1) OWNER: Name CAMA BEACH STATE PARK Address WEST CAMANO DRIVE CAMAND ISLAND, WA 98292-(1) OWNER: Name CAMA BEACH STATE PARK (2) LOCATION OF WELL: County ISLAND

(2a) STREET ADDRESS OF WELL (or nearest address) WEST CAMANO DRIVE

(10) WELL LOG 31-2E-265 Formation: Describe by color, character, size of material (4) TYPE OF WORK: Owner's Number of well and structure, and show thickness of aguifers and the kind and nature of the material in each stratum penetrated, with (If more than one) Method: ROTARY at least one entry for each change in formation. ______ (5) DIMENSIONS: Drameter of well 6 inches Drilled 318 ft. Depth of completed well 318 ft. FROM T0 BROWN GRAVEL SAND & SILT GRAY CLAY BROWN SAND CLAY & GRAVEL iĭ 0 30 33 42 (6) CONSTRUCTION DETAILS: Dia. from +3
Dia. from 295
Dia. from 309 30 33 42 45 53 77 88 124 216 2214 2216 2218 2218 2218 2218 2218 ft. to 285 Casing installed: WELDED ft. ft. to 299 ft. to 314 GRAY CLAY & SAND GRAY SILT SAND & GRAVEL ft. ft. 45 53 77 6 GRAY GRAVEL SAND & WATER GRAY CLAY GRAY CLAY & GRAVEL Perforations: NO 88 121 Type of perforator used SIZE of perforations BROWN GRAVEL & SAND BROWN GRAVEL SILT & SAND GRAY SILT & SAND GRAY CLAY in. by in. 124 135 206 214 ft. to ft. to ft. perforations from ft. perforations from perforations from ft. to GRAY CLAY & SAND GRAY CLAY & GRAVEL 216 278 Screens: YES Manufacturer's Name Type STAINLESS STEEL **GRAY CLAY** 280 281 281 296 298 GRAY SAND & MATER GRAY SILT & SAND Model No. n. 6 slot size 10 from 285 ft. to 290 ft.
n. 6 slot size 12 from 290 ft. to 295 ft.
packed: YES
packed: YES
size of gravel 3/4
yel placed from 314 ft. to 318 ft. Diam. 6 GRAY SAND & WATER Diam. 6 GRAY SILT GRAY SAND & WATER 310 Gravel packed: YES GRAY SAND SILT & WATER Gravel placed from 314 To what depth? 18 Surface seal: YES Material used in seal BENTONITE
Did any strata contain unusable water? NO
Type of water?

Depth of RECEIVED Depth of strata Method of sealing strata off (7) PUMP: Manufacturer's Name 9 1999 MAR H.P. Type Land-surface elevation (8) WATER LEVELS: above mean sea level ... ft.
Static level 165 ft. below top of well Date 02/03/99
Artesian Pressure lbs. per square inch Date DEPT OF EDULUGE Artesian water controlled by Completed 01/30/99 Work started 01/25/99 , men don doe experi... Complete tales... WELL CONSTRUCTOR CERTIFICATION: (9) WELL TESTS: Drawdown is amount water level is lowered below I constructed and/or accept responsibility for constatic level. struction of this well, and its compliance with all Was a pump test made? YES 1f yes, by whom? AGRA ENVIRON Yield: 35 gal./min with ft. drawdown after 24 hrs. Washington well construction standards. Materials used and the information reported above are true to my best Yield: 35 gal./min with knowledge and belief. Recovery data
Time Water Level Time Water Level Time Water Level NAME HAYES DRILLING, INC. (Person, firm, or corporation) (Type or print) ADDRESS 5696 RSHAG RD BOY NA W. The License No. 2189 Date of test hrs.